



LEVELS OF QUALITY

The lubricant SUPER LIFE 20W-50 SHPDO complies with the following international specifications:

- ACEA E7, E3
- API CI-4/CH-4
- MB 228.3
- MAN M3275
- VOLVO VDS-2/3
- MTU TYPE2
- RENAULT RVI RLD-2
- MACK EO-M PLUS
- CUMMINS CES 20076

DESCRIPTION

DUGLAS SUPER LIFE 20W-50 is a 'SHPDO' multigrade oil of multifunctional type especially recommended for all types of low emission diesel engines, ranging from the heavy drive, the earthmoving, high speed diesel and marine engines.

The quality of basic oils along with a reliable additive package guarantee an excellent behaviour in service with any types of diesel fuel and extended oil change intervals according to the information provided by Manufacturers.

DUGLAS SUPER LIFE 20W-50 can be defined as a multifunctional product to be used in all

types of fleet on high speed diesel engines, in earthmoving equipment and in all supercharged DIESEL marine engines.

The following benefits can be obtained, if you use this product:

- a higher engine cleaning,
- a better protection against piston ring sticking,
- a reduced bore polishing (exhaust pipe polishing),
- more protection against wear;
- extending oil change intervals.

TYPICAL FEATURES*

SAE Scale		20W/50
Density at 15°C.Kg./dm3	ASTM D1298	0.885
Viscosity at 100°C.cSt	ASTM D445	17.0
Viscosity Index	ASTM D2270	138
Flammability V.A.°C	ASTM D92	224
Pour Point °C	ASTM D97	-25
TBN mgKOH/g	ASTM D 2896	9

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

