



## ATF DEXRON IID

REV.2 OF 04/2021

### LEVELS OF QUALITY

The lubricant ATF DEXTRON IID complies with the following international specifications:

- GM DEXRON IID
- ZF TE-ML 02F, 03D, 04D, 09A, 11A, 11B, 14A, 17C
- VOITH 55.6335.32 (G607)
- MAN 339D
- ALLISON C4
- CAT TO-2
- MB 236.1-236.7
- FORD MERCON M2C 138CJ

### PRODUCT DESCRIPTION

Duglas Oil ATF DEXRON IID is a lubricant recommended for automatic transmissions, power steering, hydraulically assisted steering and torque converters, whenever it is required a DEXRON II D product.

It is also used as a hydraulic oil covering a large temperature range for applications in the automotive, industry and marine field.

### APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance.

Thanks to the above mentioned features it also ensures both a low pour point and a reduced foaming tendency.

### TYPICAL FEATURES\*

Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-27

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

