



ATF DEXRON III

REV.2 OF 04/2021

LEVELS OF QUALITY

The lubricant ATF DEXTRON III complies with the following international specifications:

- GM DEXRON III, IIIG
- MB 236.5, 236.9
- ZF TE-ML 02F, 03D, 04D, 09B, 11B, 14A, 17C
- VOITH G607
- FORD MERCON V
- ALLISON C-4
- CAT TO-2

PRODUCT DESCRIPTION

Duglas Oil ATF DEXRON III is a fluid produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III.

It is also used as a hydraulic oil over a large temperature range for applications in the automotive, industry and marine field.

APPLICATIONS

It ensures excellent performances in terms of:

- frictional properties;
- thermal-oxidative stability;
- wear and corrosion resistance;
- foaming resistance;
- compatibility with components for automatic transmissions, elastomer seals and plastic parts.

Thanks to the above mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

TYPICAL FEATURES*

Density at 15°C.Kg./dm3	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	150
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-30

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

