



GREASE L00 EP

PERFORMANCES

- N.L.G.I. 00
- ISO-L-X-BCHA EP

DESCRIPTION

The grease Douglas Oil GREASE L00 EP is produced by using highly selected mineral oils, lithium soap thickeners and extreme pressure additives

Multi-purpose grease which can be used in all applications whenever remarkable EP (extreme pressures) properties and high shock loads with automatic greasing systems are required.

Furthermore, it provides a good oxidation resistance and a good structural stability.

APPLICATIONS

The grease Douglas Oil GREASE L00 EP is used as a multifunctional grease in all those industrial applications subject to tough loading conditions and is used for the centralized and manual lubrication of plain and rolling bearings and sliding guides.

It has the following features:

- a good protection against rust and corrosion even with humidity,
- high EP performances
- a long life,
- a good protection against wear,

TYPICAL FEATURES *

| GREASE L00 EP | Method | 00 |
|---|-------------|---------|
| Thickener | | Lithium |
| Colour | | Ambra |
| NLGI Grade | | 00 |
| Worked penetration, dmm | ASTM D- 217 | 400-430 |
| Timken load, kg | ASTM D 2509 | 22 |
| Viscosity index of component oils, cSt a 40°C | ASTM D 445 | 100 |
| Mechanical stability (dmm) | ASTM D 1831 | 20 |
| Dropping point, °C (MIN.) | ASTM D 2265 | 180 |

(*)The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

