



PERFORMANCES

- N.L.G.I. 2
- ISO-L-X-BCHA

DESCRIPTION

The grease Douglas Oil GREASE L2 is produced by using highly selected mineral oils and lithium soap thickeners.

Multi-purpose grease which can be used in all applications, whenever remarkable EP (extreme pressures) properties and high shock loads are not required.

Furthermore, it provides a good oxidation resistance and a good structural stability.

APPLICATIONS

The grease Douglas Oil GREASE L2 is used as a multifunctional grease in all those industrial applications subject to mean loading conditions and is used for the centralized and manual lubrication of plain and rolling bearings and sliding guides. It has the following features:

- a good protection against rust and corrosion even with humidity,
- a long life,
- a good protection against wear,
- recommended operating temperatures: -20°C to +170 °C.

TYPICAL FEATURES*

GREASE L2	Method	2
Thickener		Lithium
Colour		Amber
NLGI Grade		2
Worked penetration	ASTM D- 217	275-295
Timken load, kg	ASTM D 2509	16
Oil viscosity, cSt at 40°C	ASTM D 445	150
Mechanical stability (dmm)	ASTM D 1831	15
Dropping point, °C (MIN.)	ASTM D 2265	170

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

