



## GREEN 4T 15W-30

### LEVELS OF QUALITY

The lubricant GREEN 4T 15W-30 complies with the following international specifications:

- API SG, CD
- ACEA A2

### PRODUCT DESCRIPTION

Multigrade lubricants which are specifically designed to ensure the maximum performance of small 4 stroke petrol engines for agricultural machineries and brush cutters. It has been formulated with additives which reduce the formation of deposits, lacquers, and sludges both at low and high temperatures.

### APPLICATIONS

GREEN 4T 15W-30 can be used in all 4 stroke engines of which are provided the small agricultural machineries and brush cutters characterized by high operating modes. Furthermore, it offers protection against rust, wear and corrosion and reduces the oxidation at high temperatures.

### TYPICAL FEATURES\*

SAE Scale	15W-30
Density at 15°C.Kg./dm3 ASTM D1298	0.860
Viscosity at 100°C.cSt ASTM D445	10,5
Viscosity Index ASTM D2270	140
Flammability V.A.°C ASTM D92	210
Pour Point °C ASTM D97	-24
T.B.N. ASTM D2896	7

\*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

