



LEVELS OF QUALITY

The lubricant GTs 10W-40 complies with the following international specifications:

- API SL, SJ, CF
- ACEA A3/B3, A3/B4
- MB 229.1
- VW 500.00, 501.01, 505.00

DESCRIPTION

Duglas Oil GTs 10W-40 is a semi-synthetic multigrade lubricant produced by using high-quality components.

It has been developed for modern concept petrol and diesel engines with high performance and extended replacement intervals.

It offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale		10W/40
Density at 15°C.Kg./dm3	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	13.3
Viscosity Index	ASTM D2270	150
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	10.2

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

