



LEVELS OF QUALITY

The lubricant GTs EVO-SYNT 5W-50 complies with the following international specifications:

- API SN, SM, CF
- ACEA A3/B4
- VW 501.01, 502.00, 505.00
- MB 229.3, 229.5
- BMW LONG LIFE 01
- GM-LL-B-025
- RENAULT RN0700, RN0710
- PORSCHE A40

DESCRIPTION

Duglas Oil GTs EVO-SYNT 5W-50 is a synthetic lubricant produced using the highest formulation levels, designed to provide excellent performances in modern petrol and diesel engines able to satisfy the requirements of new concept supercharged engines and useful for the use in catalysed engines fuelled with LPG.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale	5W/50
Density at 15°C.Kg./dm3 ASTM D1298	0.865
Viscosity at 100°C.cSt ASTM D445	17.0
Viscosity Index ASTM D2270	155
Flammability V.A.°C ASTM D92	214
Pour Point °C ASTM D97	-33
T.B.N. ASTM D2896	10.2

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

