



LEVELS OF QUALITY

The lubricant GTs ULTRA-SYNT 5W-40 complies with the following international specifications:

- ACEA A3/B3
- API SL, SJ, CF
- VW 502.00, 505.00
- MB 229.1

DESCRIPTION

Duglas Oil GTs ULTRA-SYNT 5W-40 is a synthetic-based multigrade oil for petrol and diesel engines able to satisfy the requirements of new concept supercharged engines and useful for the use in catalysed engines fuelled with LPG.

The high viscosity index allows use under any climatic conditions (low and high external temperatures).

It provides the maximum protection for engines and guarantees the right viscosity under any operating conditions (cold starts, long distances, etc.).

It is recommended to always observe the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale		5W/40
Density at 15°C.Kg./dm3	ASTM D1298	0.860
Viscosity at 100°C.cSt	ASTM D445	13.5
Viscosity Index	ASTM D2270	145
Flammability V.A.°C	ASTM D92	210
Pour Point °C	ASTM D97	-30
T.B.N.	ASTM D2896	8

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

