

OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GTv CLEAN C3 5W-40



REV.4 OF 04/2021

LEVELS OF QUALITY

The lubricant GTv CLEAN C3 5W-40 complies with the following international specifications:

- > API SN, SM, CF
- > ACEA C3
- MB 229.51, 229.31, 226.5
- ▶ BMW LONG LIFE 04
- FORD WSS-M2C917A

DESCRIPTION

Duglas Oil GTv CLEAN C3 5W-40 is a 100% synthetic lubricant with low ash content (MID SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

- VW 502.00, 505.00, 505.01
- PORSCHE A40

É

- GM DEXOS 02
- FIAT 9.55535.S2, GH2
- RENAULT RN0700, RN0710
- PSA B71 2297

Furthermore, Duglas Oil GTv CLEAN C3 5W-40 has been specifically designed to satisfy the latest ACEA C3 specifications with a mid-ash content and is recommended for engines equipped with particulate filtration systems, maintenance-free and without fuel additives

TYPICAL FEATURES

SAE Scale	5W/40
Density at 15°C.Kg./dm3 ASTM D1298	0.850
Viscosity at 100°C.cSt ASTM D445	13.2
Viscosity Index ASTM D2270	155
Flammability V.A.°C ASTM D92	218
Pour Point °C ASTM D97	-33
S.A. ASTM D874	0.75
T.B.N. ASTM D2896	7.4

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111 Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911 P!VA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it