



LEVELS OF QUALITY

The lubricant GTv ECO C4 5W-30 complies with the following international specifications:

- API SN, CF
- ACEA C4
- MB 229.51, 226.51
- RENAULT RN0720
- BMW LL-04

DESCRIPTION

Duglas Oil GTv ECO C4 5W-30 is a 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged. It is especially recommended for vehicles of Renault and Daimler groups (MB, Smart). It is recommended to observe always the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES

SAE Scale		5W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	12
Viscosity Index	ASTM D2270	160
Flammability V.A. °C	ASTM D92	210
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.49
T.B.N.	ASTM D2896	6

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

