



### LEVELS OF QUALITY

The lubricant GTv MAX C3 5W-30 complies with the following international specifications:

- API SN, SM, CF
- ACEA C3
- MB 229.52, 229.51, 229.31, 226.5
- BMW LONG LIFE 04
- VW 502.00, 505.00, 505.01
- PSA B71 2297
- PORSCHE C30
- GM DEXOS 02
- FIAT 9.55535.S2, S3

### DESCRIPTION

Duglas Oil GTv MAX C3 5W-30 is a LONG LIFE 100% synthetic lubricant with low ash content (Mid SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Duglas Oil GTv MAX C3 5W-30 has been specifically designed to satisfy the latest ACEA C3 specifications and is recommended for motorizations fitted with particulate filtration systems, are maintenance-free and without fuel additives.

### TYPICAL FEATURES

SAE Scale		5W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	11.8
Viscosity Index	ASTM D2270	150
Flammability V.A. °C	ASTM D92	216
Pour Point °C	ASTM D97	-36
S.A.	ASTM D874	0.79
T.B.N.	ASTM D2896	6.8

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

