



LEVELS OF QUALITY

The lubricant GTv POWERGAS 5W-40 complies with the following international specifications:

- API SN, SM
- ACEA C3
- FIAT 9.55535-T2

DESCRIPTION

GTv POWERGAS 5W-40 is a fully synthetic lubricant designed for petrol engines, also turbocharged, powered with methane or LPG. Its exclusive formulation improves valve protection against wear, neutralizes the acid compounds formed by the combustion and keeps engine performance level.

GTv POWERGAS 5W-40 has a special formula that, contributes to obtain, through the blow-by fumes, the best characteristics of adhesiveness, anti-wear and cleansing at the interface between valve and valve seat.

The elevated starting value of the TBN contribute to neutralize the oil acidity, avoiding the chemical aggression of the parts during the whole drain interval.

GTv POWERGAS 5W-40 meets:

- Resistance to wear for the tappets (new special additive)
- Low viscosity to improve the cold start
- Fuel economy
- Greater protection for modern TWC
- In force also for Euro 5 engine

TYPICAL FEATURES

SAE Scale		5W/40
Density at 15°C.Kg./dm3	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	13.5
Viscosity Index	ASTM D2270	160
Flammability V.A. °C	ASTM D92	218
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.75
T.B.N.	ASTM D2896	7.9

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

