



GTv ULTRALIGHT FE 0W-20

REV.3 OF 04/2021

LEVELS OF QUALITY

The lubricant GTv ULTRALIGHT FE 0W-20 complies with the following international specifications:

- API SN
- ACEA C2, A1/B1
- VOLVO VCC RBSO-2AE
- FIAT 9.55535-DSX, GSX
- BMW LL-14 FE+
- ILSAC GF-5

DESCRIPTION

GTv ULTRALIGHT FE 0W-20 is a lubricant specially designed for highly stressed downsized engines with maximum power output, for extreme fuel economy characteristics and reduced CO2 emissions. Excellent cold starting behavior, very fast oil circulation and outstanding performance reserves.

Due to its characteristics GTv ULTRALIGHT FE 0W-20 is predominantly used in Euro V and EURO VI engines where an ACEA A1/B1 engine oil is specified.

GTv ULTRALIGHT FE 0W-20 has been specially developed and approved for use in the new VOLVO VEA (Volvo Engine Architecture) engine generation.

As GTv ULTRALIGHT FE 0W-20 will be our basis for new engine designs good biofuel compatibility is provided.

TYPICAL FEATURES

SAE Scale		0W/20
Density at 15°C.Kg./dm3	ASTM D1298	0.840
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.5

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

