



LCA

REV.2 OF 04/2021

LEVELS OF QUALITY

The lubricants of the series LCA comply with the following levels of quality:

- Vickers V104C
- DIN 51506 VD-L

DESCRIPTION

The series of LCA oils are suitable for the lubrication of rotary, centrifugal and screw air compressors, for which a lower viscosity (32/46) is recommended; they are also suitable for the lubrication of single and multi-stage alternative compressors, working at very high pressures (up to 1000 bar), for which a higher viscosity (68 to 150) is recommended. They can be also used for rotary vane compressors with a 100-150 viscosity.

LCA oils have remarkable EP features which make them suitable for the use under extreme conditions for the maximum temperature of 220°C.

They also show an excellent oxidation and corrosion resistance.

When you choose the oil characteristics to be used, it is recommended to always follow the manufacturer's recommendations.

TYPICAL FEATURES*

ISO VG	32	46	68	100	150
Density at 15°C.Kg./dm3 ASTM D1298	0,872	0,880	0.885	0.900	0.900
Viscosity at 40°C.cSt ASTM D445	28.8 to 35.2	41.4 to 50.6	61.2 to 74.8	90 to 110	135 to 165
Viscosity at 100°C.cSt ASTM D445	5.3	7.0	8.7	11.5	14.3
Viscosity Index ASTM D2270	114	110	107	105	95
Flammability V.A.°C ASTM D92	216	230	236	250	260
Pour Point °C ASTM D97	-12	-12	-12	-12	-9

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it