



LEVELS OF QUALITY

The lubricant Douglas Oil OUTBOARD 2T complies with the following international specifications:

- NMMA TCW-III

DESCRIPTION

A special pre-diluted and ashless oil of the latest formulation for two-stroke outboard engines which complies with the NMMA TC-W3 specification, thus providing an excellent lubricating power and protection against piston ring sticking and sizing.

As this is a pre-diluted product it ensures an instant homogeneous blend even at low environmental temperatures.

APPLICATIONS

Its specific formulation ensures a perfect lubricant dispersion inside lead-free petrol engines, by improving the combustion and the efficiency of the engine.

The following benefits can be obtained if you use this product:

- reduction in smoke coming from the exhaust pipe.
- a higher engine cleaning.

It ensures the highest performance of blends: 100:4 (4%). However, follow the Manufacturer's indications.

TYPICAL FEATURES*

Density at 15°C.Kg./dm3	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	8.0
Colour	visual	BLUE
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-18

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

