



LEVELS OF QUALITY

The lubricant Douglas Oil OUTBOARD 4T 15W-40 complies with the following international specifications:

- API SM
- JASO MA2

DESCRIPTION

Douglas Oil OUTBOARD 4T 15W-40 is a high-performance lubricant; its formula ensures the highest levels of engine protection covering a large range of uses which are typical of outboard engines, i.e. from high-speed navigation to long operating cycles idling.

It provides reliability properties and steady performances by keeping the oil film stable, also with high levels of fuel dilution maintaining a high resistance to viscosity losses of the oil.

APPLICATIONS

Douglas Oil OUTBOARD 4T 15W-40 has been formulated for all four-stroke outboard engines for major American and Japanese manufacturers.

Its particular formulation provides:

- a reduced oil consumption and piston cleaning.
- maximum protection of the distribution system thanks to its remarkable anti-wear characteristics even at low temperatures.
- good anti-corrosion characteristics offering safe protection even during the Winter garaging.

TYPICAL FEATURES*

SAE Scale	15W/40
Density at 15°C.Kg./dm ³ ASTM D1298	0.875
Viscosity at 100°C.cSt ASTM D445	14.0
Viscosity Index ASTM D2270	135
Flammability V.A.°C ASTM D92	220
Pour Point °C ASTM D97	-27
T.B.N. ASTM D2896	8

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

