



LEVELS OF QUALITY

The lubricant Douglas Oil STS POWER SYNT MIX 2T complies with the following international specifications:

- API TC PLUS
- JASO FC
- ISO-L-EGD

DESCRIPTION

The lubricant Douglas Oil STS POWER SYNT MIX 2T is formulated with synthetic technology and it can be used in motorcycle and scooter engines with automatic or separate blending. Furthermore, it can be used in two-stroke engines installed on agricultural machineries and in two-stroke engines of mowers and motor saws.

The special additives and synthetic base used offer a good scratch protection of pistons, an effective anti-wear action and a good protection against spark plug clogs.

APPLICATIONS

Its specific formulation ensures a perfect lubricant leakage inside lead-free petrol engines, by improving the combustion and the efficiency of the engine.

The following benefits can be obtained if you use this product:

- reduction in smokes coming from the exhaust pipe.
- a higher engine cleaning.

TYPICAL FEATURES

Density at 15°C.Kg./dm3	ASTM D1298	0.860
Viscosity at 100°C.cSt	ASTM D445	10.5
Colour	visual	amber
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-24

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

