



LEVELS OF QUALITY

The lubricant SUPER LIFE 10W-40 SHPDO complies with the following international specifications:

- ACEA E3, E5, E7, A3/B4
- API CI-4, SL
- MB 228.3, 229.1
- MAN M3277
- VOLVO VDS-3
- MTU TYPE2
- RENAULT RVI RLD-2
- CAT ECF-2
- MACK EO-M PLUS
- CUMMINS CES 20077

PRODUCT DESCRIPTION

Duglas Oil SUPER LIFE 10W-40 is a multigrade oil based on the latest concept synthetic technology designed to satisfy the requirements of the latest versions of supercharged diesel engines with extended oil change intervals and at low emissions with EURO V technologies.

The quality of basic oils along with a reliable additive package guarantee an excellent behaviour in service with any types of diesel fuel and extended oil change intervals according to the information provided by Manufacturers.

Duglas Oil SUPER LIFE 10W-40 can be defined as a multifunctional product to be used in all types of fleets on high-speed diesel engines, in earthmoving equipment and in all supercharged DIESEL marine engines.

The following benefits can be obtained if you use this product:

- a higher engine cleaning.
- a better protection against piston ring sticking.
- a reduced bore polishing (exhaust pipe polishing).
- more protection against wear.
- extending oil change intervals.

It is recommended to observe always the oil change interval as suggested by the car manufacturer.

TYPICAL FEATURES*

SAE Scale	10W/40
Density at 15°C.Kg./dm ³ ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	13.5
Viscosity Index ASTM D2270	145
Flammability V.A.°C ASTM D92	218
Pour Point °C ASTM D97	-30
TBN mgKOH/g ASTM D 2896	9

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

