



LEVELS OF QUALITY

The lubricant SUPER TURBO E3 15W-40 HPDO complies with the following international specifications:

- ACEA E3, A3/B3
- API CI-4, CG-4, CF-4
- MB 228.3
- MAN M3275
- DEUTZ DQC-II 05
- MTU TYPE2
- RENAULT RD
- CAT TO-2
- ZF TE-ML-04 C

DESCRIPTION

Duglas Oil TURBO E3 15W-40 is a 'HPDO' multigrade oil of multifunctional type especially recommended for all types of diesel engines, ranging from the heavy drive, the earthmoving, high speed diesel and marine engines.

The quality of basic oils along with a reliable additive package guarantee an excellent behaviour in service with any types of diesel fuel and extended oil change intervals according to the information provided by Manufacturers.

Duglas Oil SUPER TURBO E3 15W-40 can be defined as a multifunctional product to be used in all types of fleets on high-speed diesel engines, in earthmoving equipment and in all supercharged DIESEL marine engines.

The following benefits can be obtained if you use this product:

- a higher engine cleaning,
- a better protection against piston ring sticking,
- a reduced bore polishing (exhaust pipe polishing),
- more protection against wear.
- extending oil change intervals.

TYPICAL FEATURES*

SAE Scale		15W/40
Density at 15°C.Kg./dm3	ASTM D1298	0.875
Viscosity at 100°C.cSt	ASTM D445	14.0
Viscosity Index	ASTM D2270	140
Flammability V.A.°C	ASTM D92	220
Pour Point °C	ASTM D97	-27
TBN mgKOH/g	ASTM D 2896	10.5

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

