



LEVELS OF QUALITY

The lubricant U.T.T.O. 80W / 10W-30 complies with the following international specifications:

- API GL-4
- ALLISON C4
- CAT TO-2
- FORD M2C 134D
- JD J20C
- CNH MAT 3525, 3526
- KUBOTA UDT
- MF CMS M1143, M1135, M1145
- ZF TE-ML 03E, 05E
- VOLVO WB101

PRODUCT DESCRIPTION

Multifunctional lubricant (U.T.T.O. – Universal Tractor Transmission Oil) for hydraulic transmissions and systems of tractors and agricultural machineries in general.

It provides high anti-wear properties, anti-stick and anti-slip properties which allow the best effectiveness of the braking system. The high viscosity index guarantees the reaction of servocontrols under all temperature conditions. Furthermore, the formulation guarantees a reduction in power consumption and improves the efficiency of the hydraulic circuit.

APPLICATIONS

U.T.T.O. 80W / 10W-30 is a multifunctional product to be used on gear changes, brake transmissions and oil bath, lateral reducers, wheel reducers, differential gears, hydraulic lifts, driving pulley, mechanical and hydrostatic guide of all agricultural machineries and earthmoving equipment, whenever a product complying with newer versions of the specification is required.

TYPICAL FEATURES*

SAE Scale	800W/10W-30
Density at 15°C.Kg./dm3 ASTM D1298	0.870
Viscosity at 100°C.cSt ASTM D445	10.5
Viscosity Index ASTM D2270	135
Flammability V.A.°C ASTM D92	205
Pour Point °C ASTM D97	-27

*The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

