



GTv LITE 0W-30 C2

REV.1 Di 04/2021

LEVELS OF QUALITY

The lubricant GTv LITE 0W-30 C2 complies with the following international specifications:

- API SN
- ILSAC GF-5
- ACEA C2
- FORD WSS-M2C950-A
- FIAT 9.55535-DS1, GS1
- PSA B71 2312
- BMW LL-12 FE
- STJLR 03.5007

DESCRIPTION

Duglas Oil GTv LITE 0W-30 C2 is a 100% synthetic Mid Saps lubricant designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The low viscosity and the high viscosity index help to provide maximum assistance to the engine during the starting even at low temperatures.

Duglas Oil GTv LITE 0W-30 C2 is specially produced to satisfy ACEA C2 specifications and is suitable for engines with anti-particulate filters (DPF, TWC, FAP) without manutention or fuel additives. The low ash content helps to extend the engine's life too.

TYPICAL FEATURES

SAE Scale		0W-30
Density at 15°C.Kg./dm3	ASTM D1298	0.852
Viscosity at 100°C.cSt	ASTM D445	10.3
Viscosity Index	ASTM D2270	168
Flammability V.A. °C	ASTM D92	200
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.8
T.B.N.	ASTM D2896	7.5

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it