



LEVELS OF QUALITY

POWER-Tech 10W-40 4T complies with the following international specifications:

- API SM
- JASO MA2

DESCRIPTION

DuglasOil POWER-Tech 10W-40 4T is an oil made on a synthetic base with the use of high-quality additives. Designed for water or air-cooled 4-stroke motorcycle and scooter engines, compared to traditional oils, it offers superior performance in terms of thermal stability, viscometric characteristics and fluidity at low temperatures. Provides excellent performance on all types of 4-stroke engines, both high power and racing; suitable for the lubrication of gearboxes and oil bath clutches, recommended for use in small 4-stroke engines of generators and in the agricultural sector.

APPLICATIONS

The special formulation guarantees excellent protection both at high temperatures, in severe operating conditions and when starting with a cold engine.

The use of this product allows the following benefits to be obtained:

- Reduction of exhaust smoke
- Cleaner engine.
- reduction in wear of rings and pistons.

TYPICAL FEATURES *

SAE SCALE		10W-40
Density at 15°C Kg/dm ³	ASTM D1298	0,850
Viscosity at 100°C cSt	ASTM D445	14,5
Viscosity Index	ASTM D2270	150
Flammability V.A. °C	ASTM D92	210
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	10

* The above-mentioned values are indicative of production average values and are not an integral part of the specification

RA.M.OIL S.p.A.

Sede Legale: Riviera di Chiaia, 256 - 80121 Napoli (NA)

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 16.000.000,00 int. vers.

info@ramoil.it - ramoil@pec.ramoil.it - www.ramoil.it

