

DUGLAS OIL

LUBRIFICANTI PER MOTO / MOTORCYCLE LUBRICANTS

PRO-Tech 10W-60 4T

Rev.1 of 07/2024

LEVELS OF QUALITY

PRO-Tech 10W-60 4T complies with the following international specifications:

- API SM
- JASO MA2
- Recommended for: HONDA, YAMAHA, SUZUKI, KAWASAKI, DUCATI, BMW, APRILIA

DESCRIPTION

DuglasOil PRO-Tech 10W-60 4T is an oil made on a 100% synthetic PAO type base, with the use of very high-quality additives. Designed for water or air-cooled 4-stroke motorcycle and scooter engines, compared to traditional oils, it offers superior performance in terms of thermal stability, viscometric characteristics and fluidity at low temperatures. Provides excellent performance on all types of 4-stroke engines, both high power and racing; suitable for the lubrication of gearboxes and oil bath clutches.

APPLICATIONS

Designed to meet the needs of the major manufacturers in the motorcycle field, thanks to the special formulation it guarantees excellent protection both at high temperatures, in severe operating conditions and when starting with a cold engine.

The use of this product allows the following benefits to be obtained:

- Reduction of exhaust smoke
- Cleaner engine.
- Reduced wear of rings and pistons.

TYPICAL FEATURES *

SAE SCALE		10W-60
Density at 15°C Kg/dm ³	ASTM D1298	0,860
Viscosity at 100°C cSt	ASTM D445	24,5
Viscosity Index	ASTM D2270	175
Flammability V.A. °C	ASTM D92	224
Pour Point °C	ASTM D97	-30
T.B.N.	ASTM D2896	10

* The above-mentioned values are indicative of production average values and are not an integral part of the specification

RA.M.OIL S.p.A.

Sede Legale: Riviera di Chiaia, 256 - 80121 Napoli (NA)

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 16.000.000,00 int. vers.

info@ramoil.it - ramoil@pec.ramoil.it - www.ramoil.it